

Alkaline solution for immediate and total elimination of OMBRAFLEX REVERSO.

- CONCENTRATED.
- SUITABLE FOR PLASTIC AND GLASS GREENHOUSES.
- SPRAY APPLICATION.
- BIODEGRADABLE RESIDUES.



PRODUCT IDENTIFICATION

DEFINITION

sprayable alkaline solution to remove shade paint **OMBRAFLEX REVERSO** applied on large glass or plastic areas.

CHARACTERISTICS

- Thinner: water.
- Density: 1,07 ± 0,05 kg/dm³. - pH > 12. Alkaline product.
- Reaction time: 20 to 30 minutes depending on the quantity and weather.
- Drying time (at 23°C and RH = 50 %): 1 to 3 hours.
- Optimal rinsing time: 2 days
- Flash point: non-flammable, water-based product.
- In-can aspect: translucent and thick product.

QUALITY CONTROL

the above characteristics are given by reference to standards relevant for the FPC (Factory Production Control). This FPC is carried out according to certified quality & environmental management ISO 9001 (2015) and ISO 14001 (2015).

DESCRIPTION

Washing solution suitable for:

- perfect spray of the product,
- good impregnation of the remaining coatings,
- a reaction time long enough to work on large surfaces.

Elimination of residues and cleaning of surfaces treated with water under low pressure, or by heavy rain occurring within 2 or 3 days after spraying.

CAUTION

- Do not apply by temperatures below 5°C and with Relative Humidity (RH) above 80%, during frosty weather conditions, direct sunlight or in high winds.
- Wear necessary personal protective equipment (PPE): gloves and goggles during preparation and spraying of the product.
- Protect surrounding crops from sprays.
- Dispose of waste water responsibly.

USES

WORKS: maintenance.

DESTINATION: greenhouses (horticulturists, market gardeners, etc.), industrial glass-roof, glazing.

LOCATION: exterior.

SPREADING RATE:

OMBRASTOP REVERSO	Thinning with water	Practical coverage
1 volume	7 volumes	12 to 15 m ² /litre
20 kg	140 litres	1900 to 2300 m ²

APPLICATION MODE

THINNING: 1 volume d'OMBRASTOP REVERSO for 7 volumes of water.

TOOLS: For small areas, a garden sprayer of twenty litres is suitable. Large areas will be treated by all types of sprayers.

TOOLS CLEANING: with water, immediately after use.

APPLICATION: Spray the solution obtained regularly in one or more passes taking care that the product does not flow and is not sprayed onto the crops.

RINSING

- Apply OMBRASTOP REVERSO and wait for the product to become completely mat (between 1 to 3 hours after the application).
- Within 2 days, remove residues by rinsing with clear water under pressure or jet: pump, tractor atomizer, etc. Heavy rain may also be suitable.
- After rinsing, if traces persist, repeat the cleaning operation on the concerned areas and if necessary, provide for the elimination of residues by manual action (brushing with clean water).
- Dispose of waste water responsibly.

PACKAGING

PACKAGING: 20 L (bucket)

HEALTH, SAFETY & ENVIRONMENT

Safety datasheets: available on www.ombraflex.com or www.quickfds.fr.

THIS PRODUCT IS CORROSIVE.

The consultation of the OMBRASTOP REVERSO Safety Data Sheet (SDS) remains essential for a good use of the products before and during the works.

OTHER INFORMATION

Shelf life: 12 months in its original unopened packaging kept away from humidity, frost and heat.

Waste treatment: dangerous waste. In case of leftover product, please dispose of it responsibly (depends on national regulation).

GENERAL TERMS OF USE

This product, namely a coating product, is a consumer good. The given information results from tests in compliance with relevant regulations and standards. The user shall check before applying that the product is suitable for the intended use, and that the present datasheet is the latest updated version available.

Refer also to general terms of sales.



Pour la France : ALLIOS SAS • Les Docks II • 185 Chemin de Saint-Lambert • 13821 LA PENNE-SUR-HUVEAUNE
Tél. : 04 96 12 50 00 - Fax : 04 91 47 80 65 - e-mail : contact@ombraflex.com
Pour l'export : ALLIOS SAS 2648, RD 6007 - 06270 VILLENEUVE-LOUBET - France
Tél.: +33 4 92 02 66 61 - Fax: + 33 4 92 02 66 59 - e-mail: service.export@allios.fr